

HUNTSMAN

Enriching lives through innovation

Protecting connections

TPU elastomers
for Wire & Cable
applications







Experts in elastomers

Our polyurethanes business division is a leading developer of polyurethane (PU) and thermoplastic polyurethane (TPU) materials. Combining global reach with decades of experience in material innovation, we are experts in urethane-based elastomers and have in-depth knowledge of their application across a vast range of industries.

A flexible partner for wire & cable producers

We have a 20-year track record in delivering high quality TPU elastomers optimized to perform in a wide range of wire and cable applications. Fast and flexible when responding to customers' needs, we form long-lasting connections with wire and cable companies worldwide, who trust us to deliver:

- Special products for flame retardant (FR) applications
- Products that comply with halogen-free, RoHS and REACH regulations
- A range of materials with matt, glossy or transparent finishes
- FDA / FCM / NSF approved materials produced under strict good manufacturing practice (GMP) conditions
- TPU materials that are intrinsically recyclable.

Protecting connections

Flexible and light, yet strong and durable, our polyether-based materials are designed to help protect connections in the most challenging conditions.

General characteristics include:

- A wide processing window
- High extrusion speeds
- Ductile down to -50°C
- Stable and flexible from -50 to 120°C
- Consistent dimensional integrity
- Antimicrobial
- Resistance to abrasion, fatigue, cuts, tears, vibration impact and kinking
- Resistance to oil and hydrolysis even at high temperatures
- Easy to color.

Specialty TPU grades

Our IROGRAN® TPU portfolio for the wire and cable industry includes specialty flame retardant, matt, transparent and high heat products as well as grades that are compliant with GMP procedures.

Recognizing the importance of offering flame retardancy, we've developed a family of high performance, halogen-free IROGRAN® FR TPUs with excellent reaction to fire, which can help overcome different design and performance challenges.





Transportation & automotive

When it comes to testing mechanical performance, cabling materials must be wear resistant, tolerant to significant temperature fluctuations, and impervious to petrol, oil, moisture and acids.

To meet these criteria, we've developed an advanced range of IROGRAN® TPU elastomers for use in wire and cable applications across the transportation industry.

Typical applications:

- Sensor cables for anti-lock braking systems (ABS)
- Cables for electronic stability program systems (ESP)
- Charger cables for hybrid and electric vehicles
- Cable harness / assembly
- Coiled cables
- Battery cables
- Cables for mass transportation.

Benefits:

- Excellent gravel resistance
- Outstanding dynamic resistance under flexion and torsion
- Ductile over a broad range of temperatures
- Low bending radii
- Extremely tough with high overall mechanical properties.

Industrial & automation



Industry 4.0 and the rise of automated production systems are changing the way things are made. Cables lie at the heart of intelligent manufacturing, powering smart factories, delivering commands to machines, and transmitting information.

Our IROGRAN® TPU elastomers for the wire and cable industry can support the digitization of manufacturing. Highly flexible yet incredibly robust, these innovative materials work equally well in static and dynamic equipment.

Typical applications:

- Flame retardant power / sensor cables for robots
- Drag chain cables
- General electric and electronic wiring systems
- Cables for elevators, lifts and escalators
- High performance portable power and extension cables
- Telecommunications cables.

Benefits:

- State-of-the-art flame retardancy
- Oil and chemical resistance
- Low-friction jacket surface to make cable replacement easy.

Energy & offshore

We've channeled our knowledge of the wire and cable industry to develop a range of heavy duty IROGRAN® TPU elastomers for use across the world's energy markets - from offshore wind farms to oil platforms and mining environments.

Typical applications:

- Geophysical cables and subsea umbilicals
- Control cables for windmills and turbines
- Power cables for mining and offshore equipment
- Solar panel cables.

Benefits:

- Low temperature ductility
- Abrasion resistance
- Weathering and oil resistance
- Outstanding flame retardancy.

Consumer goods

In our connected world, wires and cables need to deliver a continuous flow of information and power. These vital links are required 24 hours a day, seven days a week – so failure is not an option.

Our IROGRAN® TPUs can be used to create reliable, robust cable jackets for the transmission of data and audio signals.

Typical applications:

- USB charging cables for smart phones
- Cables for headphones.

Benefits:

- Stain resistant
- Weathering resistance
- Good reaction to fire
- Easy to color.





Medical & healthcare

Across the medical and healthcare industry, power leads for non-invasive devices, such as imaging scanners and pulse sensors, must be resistant to cleaning liquids and antibacterial gels.

We produce a range of IROGRAN® TPU elastomers under strict GMP conditions, which are suitable for medical device cabling applications. Soft, and with a rubber-like feel, these materials are easy to clean and are ideal for creating sensor, control and power cables.

Typical applications:

Cables for non-invasive medical devices such as:

- Fingertip oximeters
- Barcode scanners
- Heart monitors
- Defibrillators.

Benefits:

- Resistant to disinfectants, hygiene gels and sprays
- Easy to clean
- Flexible
- A soft touch and good grip.

Infinite scope for innovation

IROGRAN® TPUs: Key products

Physical Properties	Norm	Unit	A 75 E 5040	A 70 P 6027UV	A 80 P 5039	A 80 P 4699L	A 85 P 4394
FLAMMABILITY							
UL 94	IEC60695-11-10	-	N/A	N/A	N/A	N/A	N/A
LOI	ASTM D-2863	%	N/A	N/A	N/A	N/A	N/A
GENERAL							
Hardness	ASTM D 2240	Shore A	75	70	80	80	85
Hardness	ASTM D 2240	Shore D	25	N/A	29	31	36
Density	ASTM D 792	g/cm ³	1.15	1.07	1.10	1.10	1.12
MECHANICAL							
Tensile Strength	ASTM D-412	psi	2200	4630	5660	4600	6850
Elongation @ Break	ASTM D-412	%	650	730	620	660	560
Tensile Stress @ 100% Elongation	ASTM D-412	psi	570	475	680	610	930
Tensile Stress @ 300% Elongation	ASTM D-412	psi	950	770	1140	930	1730
Tear Strength	ASTM D-624	pli	300	320	380	420	470
Abrasion	ISO 4649	mm ³	90	N/A	30	40	25
THERMAL							
TMA Low	Huntsman	°C	150	156	145	125	150
TMA High	Huntsman	°C	190	170	155	155	170
OTHER FEATURES							
Glossy/transparent				x	x		x
Glossy/opaque							
Matte/non-tacky			x			x	
Available as UV protected				x	x		x
Available as FCM grade				x	x		x
MARKET APPLICATIONS							
Industrial							x
Transportation						x	x
Energy						x	x
Consumer Goods							
Medical & Healthcare			x	x	x		

FR TPU range for the most stringent FR applications

(UL 1581, IEC 60332-1, EN 13501-6 cable tests)

* IROGRAN® A 78 P 4766 is also available as a low migration version (NM)



A 85 P 4441	A 92 P 4637	A 92 P 4851	A 95 P 5044	A 85 P 4350	A 85 P 4380	A 78 P 4766*	A 85 P 4854	A 85 P 5090FR	A 91 P 5015FR
N/A	N/A	N/A	N/A	V2	V2	V0	V0	V0	V0
N/A	N/A	N/A	N/A	25	26	26	25	N/A	26
87	92	93	95	86	87	82	83	88	92
38	39	42	48	38	36	30	33	39	44
1.11	1.13	1.13	1.14	1.14	1.14	1.16	1.14	1.23	1.27
6960	7100	6440	8290	6030	4850	4700	3810	4300	3700
580	500	500	480	630	550	680	590	600	500
980	1300	1290	1630	460	840	700	660	1140	1370
1560	2860	2520	4050	1500	1470	1220	1170	1650	1870
480	550	580	620	360	375	340	280	14500	550
35	30	35	31	40	35	40	40	35	30
155	160	160	175	166	160	165	125	160	160
175	170	170	187	192	180	190	160	170	175
	x		x						
				x		x			
x		x			x		x	x	x
	x		x						
x	x								
x	x	x	x	x	x	x	x	x	x
x	x	x	x	x	x	x	x	x	
							x	x	x

Further technical data about individual products plus best practice advice for handling and processing our elastomers is available by contacting your local sales representative or by visiting our online product finder tool:

<http://www.huntsman-tpu.com/>

Global elastomers experts

Committed to customers: We build partnerships with our customers and work across an international network of R&D and manufacturing locations to help solve complex challenges and deliver the highest levels of technical support and customer care.

Committed to quality: Wherever we are, whatever we are doing, we prioritize environmental, health and safety protection, and we are always rigorous about quality control and assurance.

Committed to innovation: We keep pace with the most innovative trends in plastics processing by using the latest equipment and making regular investments in our formulation, manufacturing and R&D capabilities.

Committed to sustainability: We create solutions that contribute to a more sustainable society by helping to conserve energy, preserve natural resources and reduce our overall carbon footprint.



HUNTSMAN

Enriching lives through innovation

EUROPE

Hafenringstrasse 1
49090 Osnabrück
GERMANY
Phone: +49 541 914 10

Elastomers_EAIME@huntsman.com

USA

10003 Woodloch Forest Dr
The Woodlands, TX 77380
Phone: +1 281 719 6000

Elastomers_Americas@huntsman.com

CHINA

No 479 Wen Jing Road
Minhang Development Zone
Shanghai 200245
Phone: +86 21 3357 6527

Elastomers_APAC@huntsman.com

www.huntsman.com

About Huntsman:

Huntsman Corporation is a publicly traded corporation headquartered in The Woodlands, Texas, in the United States of America. Huntsman is a global downstream, differentiated, and specialty chemicals company. For more than 50 years, we have been using science and ingenuity to innovate and create products that enable more sustainable and comfortable lives for millions of people around the world. In 2023, Huntsman had more than 6,000 associates working in nearly 60 manufacturing, research and development (R&D), and operations facilities in 25 countries. Through our three divisions, we produce approximately 6,250 products to serve a broad and diverse range of consumer and industrial end markets including aerospace, transportation, building and construction, consumer goods, energy and fuels, and food preservation.

Disclaimer:

Huntsman Polyurethanes is an international business unit of Huntsman International LLC. Huntsman Polyurethanes trades through Huntsman affiliated companies in different countries such as Huntsman International LLC in the USA and Huntsman Holland BV in Western Europe. Except where explicitly agreed otherwise, the sale of products referred to in this publication is subject to the general terms and conditions of sales of Huntsman International LLC or of its affiliated companies. Huntsman warrants only that its products meet the specifications agreed with the buyer in the sales contract. Typical properties, where stated, are to be considered as representative of current production and should not be treated as specifications.

While all the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NO GUARANTY, WARRANTY OR REPRESENTATION IS MADE, INTENDED OR IMPLIED AS TO THE CORRECTNESS OR SUFFICIENCY OF ANY INFORMATION OR RECOMMENDATION OR AS TO THE MERCHANTABILITY, SUITABILITY OR FITNESS OF ANY PRODUCTS FOR ANY PARTICULAR USE OR PURPOSE. IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE. NOTHING IN THIS PUBLICATION IS TO BE CONSTRUED AS RECOMMENDING THE INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT AND NO LIABILITY ARISING FROM ANY SUCH INFRINGEMENT IS ASSUMED. NOTHING IN THIS PUBLICATION IS TO BE VIEWED AS A LICENCE UNDER ANY INTELLECTUAL PROPERTY RIGHT.

Products may be toxic and require special precautions in handling. The user should obtain Safety Data Sheets from Huntsman Polyurethanes containing detailed information on toxicity, together with proper shipping, handling and storage procedures, and should comply with all applicable safety and environmental standards. Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent on the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

IROGRAN® is a registered trademark of Huntsman Corporation or an affiliate thereof in one or more, but not all, countries. © 2024 Huntsman Corporation or an affiliate thereof. All rights reserved.